

AVISTA Flux

13.09.2021

(The given data are typical values.)

| Parameter | Test Method | Unit | Results |
|-------------------------------|-----------------------------|--------------------|--------------|
| Colour | DIN ISO 2049 ASTM D 1500 | | black |
| Density 15°C | DIN EN ISO 12185 | kg/m ³ | 870 – 900 |
| Kin. Viscosity 40°C | ASTM D 7279 DIN 51 659-3 | mm ² /s | 73 – 90 |
| Kin. Viscosity 100°C | ASTM D 7279 DIN 51 659-3 | mm ² /s | 10 – 15 |
| Flashpoint COC | DIN EN ISO 2592 | °C | > 230 |
| Sulfur content, using XRF, ed | DIN EN ISO 8754 | wt. % | < 0,50 |
| PCB | EN 12766-1; 2 (B) | ppm | LOQ* (< 5,0) |
| Ash content | DIN EN ISO 6245 | wt. % | < 1,0 |
| Water content, KF | DIN EN ISO 12937 | wt. % | ≤ 0,1 |

*below the limit of quantification

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by AVISTA OIL Deutschland GmbH for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale.