

	AVISTA OIL Deutschland GmbH	21.08.2019
Art. 153315	AVISTA Flux	Page 1 von 1

Parameter	Unit	Test Method	Typical Values
Colour			Black
Density 15°C	kg/m ³	EN ISO 12185	880 – 900
Flashpoint COC	°C	DIN ISO 2592	> 230
Viscosity 40°C	mm ² /s	ASTM D 7279	75 – 90
Viscosity 100°C	mm ² /s	ASTM D 7279	11 – 15
Ash	wt. %	EN ISO 6245	< 1.0
Water content	mg/kg	DIN EN ISO 12937	< 0.1
PCB	mg/kg	DIN EN 12 766 – 1,2	< LOQ (< 5.0)
Sulfur	wt. %	DIN EN ISO 8754	< 0.55

* limit of quantitation

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AVISTA OIL Group or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale.

Contact: AVISTA OIL Deutschland GmbH Bahnhofstraße 82, 31311 Uetze, Germany Tel. +49 5177 85-109 Fax +49 5177 85-283	File name: 154707 AVO PI AVISTA Premium Fuel 10 DE V1
--	--