



AVISTA OIL Deutschland GmbH

12.01.2018

Art. 154707

**AVISTA Fuel Premium 10**

Page 1 von 1

Parameter	Unit	Test Method	Typical Values
Colour		ISO 2049	< 6
Density 15°C	kg/m <sup>3</sup>	EN ISO 12185	850 - 860
Flashpoint PMCC	°C	EN ISO 2719	> 80
Viscosity 20°C	mm <sup>2</sup> /s	ASTM D 7279	10 - 22
Viscosity 40°C	mm <sup>2</sup> /s	ASTM D 7279	6 – 11
Sulfur	wt. %	EN ISO 8754	< 0.5
Chlorine	mg/kg	DIN 51 408 -1	< 150
Pour Point	°C	ASTM D 7346	< -15
Ash	wt. %	EN ISO 6245	0.01
PCB	mg/kg	DIN EN 12 766 – 1,2	< LOQ (< 5.0)*
Calorific Value	MJ/kg	DIN 51 900	> 42
Nitrogen	%	ASTM-D 5782	< 0,1

\* limit of quantitation

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AVISTA OIL Group or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale.

Contact:

**AVISTA OIL Deutschland GmbH**

Bahnhofstraße 82, 31311 Uetze, Germany

Tel. +49 5177 85-109 Fax +49 5177 85-283