

AVISTA ANTIFREEZE CONCENTRATE P11

(ANTIFREEZE CONCENTRATE)

PRODUCT DESCRIPTION:

AVISTA ANTIFREEZE CONCENTRATE P11 is a radiator protection agent concentrate which has to be diluted with water prior to use. It is nitrite, amine and phosphate-free. AVISTA ANTIFREEZE CONCENTRATE P11 provides frost and corrosion protection all year round for problem-free operation.

AVISTA ANTIFREEZE CONCENTRATE P11 has been especially aligned to the requirements of aluminum and cast-iron engines in cars and commercial vehicles. Specially-developed additives prevent foaming and the formation of deposits.

AVISTA ANTIFREEZE CONCENTRATE P11 is a radiator protection agent concentrate which has to be diluted with water prior to use. An application concentration of at least 50 Vol.% is recommended all year round. To be able to use the product advantages of AVISTA ANTIFREEZE CONCENTRATE P11 to their full extent, a complete coolant changes and rinsing of the affected components is recommended.

Quality Advantages:

- Product is free of nitrites, amines and phosphates
- Can be used in aluminum and cast-iron engines
- Can be mixed with other radiator protection agent concentrates with the same specifications
- Permanent protection against corrosion and cavitation
- Reliably prevents the formation of deposits
- Minimisation of foam tendencies

We cannot guarantee sufficient corrosion protection below a concentration of 33 % AVISTA ANTIFREEZE CONCENTRATE P11! The manufacturing regulations must be observed.

MEETS / SUITABLE FOR USE:

(Meets the requirements of the OEM-Approval. An approval by name from the manufacturer is not present.)

ASTM D 3306 SAE J 1034

AVISTA OIL Refining & Trading Deutschland GmbH Bahnhofstraße 82, 31311 Uetze, Germany Tel. +49 5177 85-0 Fax +49 5177 85-230







Mixing Table:

Frost protection until [°C]	Antifreeze Concentrate	Water		
-18	1	2		
-24	1	1,5		
-36	1	1		

TYPICAL CHARACTERISTICS AVISTA ANTIFREEZE CONCENTRATE P11:

(The given data are typical data. Please observe operating prescriptions.)

Parameter	Method	Unit	
Density @ 20 °C	DIN 51 757		1.12
Alkalinity Reserve	ASTM D 1121	g/cm ³	11 (pH: 5,5)
Boiling Point	ASTM D 1120	mm²/s	> 163
pH-Value	ASTM D 1287	mm²/s	7.0
Flash Point COC	DIN 51 758		> 120
Antifreeze @ 50 Vol%	ASTM D 1177	mg KOH/g	-36
Colour	In-house method	mPa*s	Light Blue

AVAILABLE PACKAGING:

	Bulk	IBC	Drum	60 Liter	20 Liter	4 * 5 Liter	4*4 Liter	12 * 1,5 Liter
AVISTA ABTIFREEZE CONCENTRATE P11			•					•

¹ Version 3 – 10/2017

AVISTA OIL Refining & Trading Deutschland GmbH Bahnhofstraße 82, 31311 Uetze, Germany Tel. +49 5177 85-0 Fax +49 5177 85-230





¹ This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AVISTA OIL or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale.